FOERSTER

MULTICAT

Large area detection system for vehicle-based large-area surveys

MULTICAT

Large area detection system for vehicle-based large-area surveys



Fast and systematic surveying of large areas. The FOERSTER MULTICAT 4.850 is a robust, non-magnetic probe carrier designed for fast and precise large-area surveys. The all-terrain system is towed by a suitable vehicle and can be equipped with up to eight FEREX MG-10-550 probes. With a fixed track width of 2 m, it enables efficient surveying of large areas.

Depending on the required measurement point density, the MULTICAT can be configured with four probes at a spacing of 0.5 m or eight probes at a spacing of 0.25 m. With the standard configuration, an area coverage of up to 2 hectares per hour can be achieved.

In combination with FEREX PNC and DATAMONITOR 4, magnetometer data is recorded with geo-referenced position information and can be visualized as a magnetic field map during the survey. The open GPS interface enables the integration of systems from various manufacturers.

Thanks to its robust design and high off-road capability, the MULTICAT is suitable for demanding large-area projects, including UXO detection as well as geological and geotechnical surveys.

YOUR ADVANTAGES AT A GLANCE

High area coverage: Surveying of up to 2 hectares per hour with the standard configuration

Flexible measurement density: Choice of 4 probes at 0.5 m spacing or 8 probes at 0.25 m spacing with a 2 m track width

Robust probe carrier system: All-terrain design for vehicle-based large-area surveys

Geo-referenced data acquisition: Precise positioning of magnetometer data using differential GPS

Real-time visualization: Display of magnetic field data during the survey with FEREX PNC and DATAMONITOR 4

High survey speed: Recommended speed of up to 10 km/h for efficient area coverage

TECHNICAL INFORMATION

DIMENSIONS (L × W × H):	5.1 × 2.5 × 0.9 m
DIMENSIONS (PACKED):	2.3 × 0.9 × 1.3 m
WEIGHT:	Approx. 150 kg
RECOMMENDED MAXIMUM SURVEY SPEED:	— 10 km/h (7 mph) — higher survey speeds possible*
TRACK WIDTH:	2 m
NUMBER OF PROBES:	— 4 at 0.5 m probe spacing — 8 at 0.25 m probe spacing
PROBE:	FEREX MG-10-550
PROBE TECHNOLOGY:	FOERSTER gradiometer probe
PROBE BANDWIDTH:	230 Hz
PROBE NOISE:	< 1 nT pp
PROBE PROTECTION GRADE:	IP68, up to 100 m with optional sealing bell
DIFFERENTIAL GPS:	Systems from various manufacturers
GPS DATA PROTOCOL:	NMEA 0183
GPS ACCURACY:	RTK FIX
CONTROLLER TECHNOLOGY:	FEREX 4.034 with 24-bit ADC
NUMBER OF PROBES PER FEREX PNC:	1–8
RECORDING RATE:	300 Hz per probe
POWER SUPPLY:	12–24 V DC
BATTERY OPERATION:	7.2 V battery pack
FEREX PNC PROTECTION GRADE:	IP65

* Depending on the operating conditions, higher survey speeds may result in increased wear of the axle bushings.

ACCESSORIES

FEREX PNC
Modular magnetometer network for large-area surveys on land and underwater

DATAMONITOR 4
Software for survey preparation, navigation and data recording for multi probe systems

FOERSTER

foerstergroup.com

The FOERSTER Group is represented by subsidiaries and representatives in over 60 countries worldwide. You can find a complete overview on our website.

Headquarters
Institut Dr. Foerster GmbH & Co. KG

In Laisen 70
72766 Reutlingen
Germany

+49 7121 140 0
info@foerstergroup.com

© Copyright 2026 – Copyright notice: All contents of this work, in particular texts, photographs and graphics, are protected by copyright. Unless explicitly stated otherwise, the copyright lies with Institut Dr. Foerster GmbH & Co. KG. Please contact us if you wish to use any part of this work.

Generated: 2026-10-11 19:37:54